



PCT/GB 0 0 / 04 0 8 3



INVESTOR IN PEOPLE

GB 00/4083

4

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

REC'D 15 NOV 2000

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

27 OCT 2000





P01/7700 0.00 - 9925522.6

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference SMC 60396/GB/P

2. Patent application number  
(The Patent Office will fill in this part)

29 OCT 1999

9925522.6

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Avecia Limited  
Hexagon House  
Blackley  
Manchester, M9 8ZS

Patents ADP number (if you know it)

~~6254007002~~

71098483001

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Compounds

5. Name of your agent (if you have one)

MAYALL, John

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Avecia Limited  
Hexagon House  
PO Box 42  
Blackley  
Manchester M9 8ZS

Patents ADP number (if you know it)

6244313002

6244313003

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

11

Claim(s)

2

Abstract

Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

*K. M. Pinder*

Date 28/10/99

Avecia Limited Authorised Signatory

12. Name and daytime telephone number of person to contact in the United Kingdom

K.M.Pinder/G.Terry 0161 721 1361/2

### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

APPLICANTS

Avecia Limited

TITLE


COMPOUNDS

## COMPOUNDS

This invention relates to dyes, to inks and to their use in ink jet printing ("IJP"). IJP is a non-impact printing technique in which droplets of ink are ejected through a fine nozzle onto a substrate without bringing the nozzle into contact with the substrate.

There are many demanding performance requirements for dyes and inks used in IJP. For example they desirably provide sharp, non-feathered images having good water-fastness, light-fastness and optical density. The inks are often required to dry quickly when applied to a substrate to prevent smudging, but they should not form a crust over the tip of an ink jet nozzle because this will stop the printer from working. The inks should also be stable to storage over time without decomposing or forming a precipitate which could block the fine nozzle.

According to the present invention there is provided a compound of Formula (1) and salts thereof:



Formula (1)

wherein:

A is a substituted phenyl group carrying a group of the formula -NR<sup>3</sup>R<sup>4</sup> and an ortho group selected from sulpho, phosphonato and phosphinato;

R<sup>1</sup> and R<sup>2</sup> are each independently optionally substituted alkyl or optionally substituted alkoxy; and

R<sup>3</sup> and R<sup>4</sup> are each independently H, optionally substituted alkyl, optionally substituted cycloalkyl or optionally substituted aryl, or R<sup>3</sup> and R<sup>4</sup> together with the N atom to which they are attached form an optionally substituted 5- or 6- membered ring.

The optional substituents which may be present on R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are preferably selected from -NH<sub>2</sub>; halo, especially Cl, Br and F; ester, especially -CO<sub>2</sub>-C<sub>1-4</sub>-alkyl; -O-C<sub>1-4</sub>-alkyl; -CO<sub>2</sub>H; -SO<sub>3</sub>H; -OR<sup>5</sup>; or -SR<sup>5</sup>; wherein each R<sup>5</sup> independently is H or C<sub>1-4</sub>-alkyl.

Preferably at least one of R<sup>1</sup> and R<sup>2</sup>, or more preferably both R<sup>1</sup> and R<sup>2</sup>, carries an -OH group.

When R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> or R<sup>4</sup> is an optionally substituted alkyl group it is preferably an optionally substituted C<sub>1-4</sub>-alkyl group, more preferably a C<sub>1-4</sub>-alkyl group or a C<sub>1-4</sub>-alkyl-OH group.

When  $R^1$  or  $R^2$  is an optionally substituted alkoxy group it is preferably an optionally substituted  $C_{1-4}$ -alkoxy group, more preferably a  $C_{1-4}$ -alkoxy or a  $C_{1-4}$ -alkoxy-OH group.

$R^1$  and  $R^2$  are preferably each independently optionally substituted  $C_{1-4}$ -alkyl or optionally substituted  $C_{1-4}$ -alkoxy, more preferably optionally substituted  $C_{1-4}$ -alkoxy, especially  $C_{1-4}$ -alkoxy-OH.


In one embodiment one of  $R^1$  and  $R^2$  is  $-OC_{1-4}$ -alkyl-OH and the other is  $-OC_{1-4}$ -alkyl or  $-OC_{1-4}$ -alkyl-OH.

When  $R^3$  or  $R^4$  is optionally substituted aryl it is preferably optionally substituted phenyl, more preferably phenyl or phenyl carrying a carboxy and/or sulpho group. When  $R^3$  and  $R^4$  together with the nitrogen atom to which they are attached form an optionally substituted 5- or 6- membered ring such ring is preferably an optionally substituted morpholino or piperidino ring

Preferably the ortho substituent is sulpho.

It is especially preferred that the group of formula  $-NR^3R^4$  is in the para position with respect to the azo linkage because this gives particularly good high optical density.

The dyes of Formula (1) may be prepared by diazotising a compound of the Formula (2) to give a diazonium salt and coupling the resultant diazonium salt with a 1-hydroxy-3-sulpho-7-aminonaphthalene:



Formula (2)

wherein A,  $R^1$  and  $R^2$  are as hereinbefore defined.

The hydroxy group(s) on  $R^1$  and/or  $R^2$  may be protected during the diazotisation, for example using an acid labile or base labile protecting group. The acetoxy protecting group is particularly convenient and inexpensive.

The diazotisation is preferably performed at room temperature or below. Preferably the diazotisation is performed in water, preferably at a pH below 7. Dilute mineral acid, e.g. HCl or  $H_2SO_4$ , may be used to achieve the desired acidic conditions.

The compound of Formula (2) may be prepared by diazotising a compound of formula  $A-NH_2$  and coupling onto an aniline compound carrying  $R^1$  and  $R^2$  groups at the 2- and 5- positions respectively, wherein A,  $R^1$  and  $R^2$  are as hereinbefore defined.

Preferred salts are alkali metal salts (especially lithium, sodium and potassium salts), ammonium and substituted ammonium salts and mixtures thereof. Especially

preferred salts are sodium, potassium and lithium salts, salts with ammonia and volatile amines and mixtures thereof. The lithium salts have good solubility, forming particularly storage stable inks with low tendency to block ink jet nozzles.

The dyes may be converted into a desired salt using known techniques. For example, an alkali metal salt of a dye may be converted into the ammonium or substituted ammonia salt by dissolving an alkali metal salt of the dye in water, acidifying with a mineral acid and adjusting the pH of the solution to pH 9 to 9.5 with ammonia or the amine and removing the alkali metal cations by dialysis or by use of an ion exchange resin.

Examples of amines which may be used to form such salts include methylamine, dimethylamine, trimethylamine, ethylamine, n-propylamine, iso-propylamine, n-butylamine, iso-butylamine, sec-butylamine, tert-butylamine, piperidine, pyridine, morpholine, allylamine, diethylamine, triethylamine and mixtures thereof. It is not essential that the dyes are completely in the form of the ammonium salt or substituted ammonium salt and mixed alkali metal and either ammonium salt or substituted ammonium salt are effective, especially those in which at least 50% of the cations are ammonium or substituted ammonium ions.

Still further salts are those with the counter ions described in US 5,830,265, claim 1, integer (b), which are included herein by reference thereto.

The dyes of Formula (1) may exist in tautomeric forms other than those shown in this specification. These tautomers are included within the scope of the present claims.

According to a second aspect of the present invention there is provided an ink comprising a compound of Formula (1) or salt thereof and a liquid medium or a low melting point solid medium.

A preferred ink comprises:

- (a) from 0.01 to 30 parts of a compound of the Formula (1) or salt thereof; and
- (b) from 70 to 99.99 parts of a liquid medium or a low melting point solid medium;

wherein all parts are by weight and the number of parts of (a)+(b)=100.

The number of parts of component (a) is preferably from 0.1 to 20, more preferably from 0.5 to 15, and especially from 1 to 5 parts. The number of parts of component (b) is preferably from 99.9 to 80, more preferably from 99.5 to 85, especially from 99 to 95 parts.

When the medium is a liquid, preferably component (a) is completely dissolved in component (b). Preferably component (a) has a solubility in component (b) at 20°C of at least 10%. This allows the preparation of liquid dye concentrates which may be used to prepare inks and reduces the chance of the dye precipitating if evaporation of the liquid medium occurs during storage.

Preferred liquid media include water, a mixture of water and an organic solvent and an organic solvent free from water.

When the liquid medium comprises a mixture of water and an organic solvent, the weight ratio of water to organic solvent is preferably from 99:1 to 1:99, more preferably from 99:1 to 50:50 and especially from 95:5 to 80:20.

It is preferred that the organic solvent present in the mixture of water and organic solvent is a water-miscible organic solvent or a mixture of such solvents. Preferred water-miscible organic solvents include C<sub>1-6</sub>-alkanols, preferably methanol, ethanol, n-propanol, isopropanol, n-butanol, sec-butanol, tert-butanol, n-pentanol, cyclopentanol and cyclohexanol; linear amides, preferably dimethylformamide or dimethylacetamide; ketones and ketone-alcohols, preferably acetone, methyl ether ketone, cyclohexanone and diacetone alcohol; water-miscible ethers, preferably tetrahydrofuran and dioxane; diols, preferably diols having from 2 to 12 carbon atoms, for example pentane-1,5-diol, ethylene glycol, propylene glycol, butylene glycol, pentylene glycol, hexylene glycol and thiodiglycol and oligo- and poly-alkyleneglycols, preferably diethylene glycol, triethylene glycol, polyethylene glycol and polypropylene glycol; triols, preferably glycerol and 1,2,6-hexanetriol; mono-C<sub>1-4</sub>-alkyl ethers of diols, preferably mono-C<sub>1-4</sub>-alkyl ethers of diols having 2 to 12 carbon atoms, especially 2-methoxyethanol, 2-(2-methoxyethoxy)ethanol, 2-(2-ethoxyethoxy)-ethanol, 2-[2-(2-methoxyethoxy)ethoxy]ethanol, 2-[2-(2-ethoxyethoxy)-ethoxy]-ethanol and ethyleneglycol monoallylether; cyclic amides, preferably 2-pyrrolidone, N-methyl-2-pyrrolidone, N-ethyl-2-pyrrolidone, caprolactam and 1,3-dimethylimidazolidone; cyclic esters, preferably caprolactone; sulphoxides, preferably dimethyl sulphoxide and sulpholane. Preferably the liquid medium comprises water and 2 or more, especially from 2 to 8, water-soluble organic solvents.

Especially preferred water-soluble organic solvents are cyclic amides, especially 2-pyrrolidone, N-methyl-pyrrolidone and N-ethyl-pyrrolidone; diols, especially 1,5-pentane diol, ethyleneglycol, thiodiglycol, diethyleneglycol and triethyleneglycol; and mono- C<sub>1-4</sub>-alkyl and C<sub>1-4</sub>-alkyl ethers of diols, more preferably mono- C<sub>1-4</sub>-alkyl ethers of diols having 2 to 12 carbon atoms, especially 2-methoxy-2-ethoxy-2-ethoxyethanol.

Examples of further suitable ink media comprising a mixture of water and one or more organic solvents are described in US 4,963,189, US 4,703,113, US 4,626,284 and EP 4,251,50A.

When the liquid medium comprises an organic solvent free from water, (i.e. less than 1% water by weight) the solvent preferably has a boiling point of from 30° to 200°C, more preferably of from 40° to 150°C, especially from 50 to 125°C. The organic solvent may be water-immiscible, water-miscible or a mixture of such solvents. Preferred water-miscible organic solvents are any of the hereinbefore described water-miscible organic solvents and mixtures thereof. Preferred water-immiscible solvents include, for example, aliphatic hydrocarbons; esters, preferably ethyl acetate; chlorinated hydrocarbons, preferably CH<sub>2</sub>Cl<sub>2</sub>; and ethers, preferably diethyl ether; and mixtures thereof.

When the liquid medium comprises a water-immiscible organic solvent, preferably a polar solvent is included because this enhances solubility of the dye in the liquid medium. Examples of polar solvents include C<sub>1-4</sub>-alcohols. In view of the foregoing preferences it is especially preferred that where the liquid medium is an organic solvent free from water it comprises a ketone (especially methyl ethyl ketone) &/or an alcohol (especially a C<sub>1-4</sub>-alkanol, more especially ethanol or propanol).

The organic solvent free from water may be a single organic solvent or a mixture of two or more organic solvents. It is preferred that when the medium is an organic solvent free from water it is a mixture of 2 to 5 different organic solvents. This allows a medium to be selected which gives good control over the drying characteristics and storage stability of the ink.

Ink media comprising an organic solvent free from water are particularly useful where fast drying times are required and particularly when printing onto hydrophobic and non-absorbent substrates, for example plastics, metal and glass.

Preferred low melting solid media have a melting point in the range from 60°C to 125°C. Suitable low melting point solids include long chain fatty acids or alcohols, preferably those with C<sub>18-24</sub> chains, and sulphonamides. The dye of Formula (1) may be dissolved in the low melting point solid or may be finely dispersed in it.

The dyes of the invention may be used as the sole colorant in inks because of their attractive black shade. They benefit from particularly good light fastness and good optical density. However, if desired, one may combine the dyes with one or more further colorants if a slightly different shade is required for a particular end use. The further colorants are preferably dyes. When further colorants are included in the ink these are preferably selected from black, cyan and yellow colorants and combinations thereof.

Preferred black colorants include C.I.Food Black 2, C.I.Direct Black 19, C.I.Reactive Black 31, Pro-Jet™ Fast Black 2, C.I.Direct Black 195; C.I.Direct Black 168; and black dyes described in patents by Lexmark (e.g. EP 0 539,178 A2, Example 1, 2, 3, 4 and 5), Orient Chemicals (e.g. EP 0 347 803 A2, pages 5-6, azo dyes 3, 4, 5, 6, 7, 8, 12, 13, 14, 15 and 16) and Seiko Epson Corporation.

Preferred cyan colorants include C.I.Direct Blue 199; C.I.Acid Blue 9; C.I.Direct Blue 307; C.I.Reactive Blue 71; and C.I.Direct Blue 85.

Preferred yellow colorants include C.I.Direct Yellow 142; C.I.Direct Yellow 132; C.I.Direct Yellow 86; C.I.Direct Yellow 85; C.I.Direct Yellow 173; and C.I.Acid Yellow 23.

However, as mentioned above, it is not normally necessary to use further colorants in conjunction with dyes of the present invention.

The ink may also contain additional components conventionally used in ink jet printing inks, for example viscosity and surface tension modifiers, corrosion inhibitors, biocides, fogation reducing additives and surfactants which may be ionic or non-ionic.

A further aspect of the invention provides a process for printing an image on a substrate comprising applying an ink containing a dye of Formula (1) to the substrate by means of an ink jet printer.

The ink used in this process is preferably as defined in the second aspect of the present invention.

Preferably the ink contains less than 500ppm, more preferably less than 100ppm, especially less than 30ppm and more especially less than 20ppm in total of divalent and trivalent metal ions. The halide content is preferably less than 500ppm, more preferably less than 250ppm. The term 'ppm' means parts per million by weight based on the total weight of ink. The metal ion and halide content may be adjusted to the desired range using any suitable technique, e.g. ultrafiltration, reverse osmosis, ion exchange or a combination thereof.

The ink may be used, as is, for ink jet printers or alternatively it may be used as a concentrate which is diluted and/or further formulated to give an ink jet printing ink. The concentrates are a useful form for transportation, avoiding the expense of transporting the water contained in finally formulated inks.

The ink jet printer preferably applies the ink to the substrate in the form of droplets which are ejected through a small orifice onto the substrate. Preferred ink jet printers are piezoelectric ink jet printers and thermal ink jet printers. In thermal ink jet printers, programmed pulses of heat are applied to the ink in a reservoir by means of a resistor adjacent to the orifice, thereby causing the ink to be ejected in the form of small droplets directed towards the substrate during relative movement between the substrate and the orifice. In piezoelectric ink jet printers the oscillation of a small crystal causes ejection of the ink from the orifice.

The substrate is preferably paper, plastic, a textile, metal or glass, more preferably paper, an overhead projector slide or a textile material, especially paper.

Preferred papers are plain or treated papers which may have an acid, alkaline or neutral character.

Preferred paper are plain or treated papers which may have an acid, alkaline or neutral character. Examples of commercially available treated papers include HP Premium Coated Paper (available from Hewlett Packard Inc), HP Photopaper (available from Hewlett Packard Inc), Stylus Pro 720 dpi Coated Paper, Epson Photo Quality Glossy Film (available from Seiko Epson Corp.), Epson Photo Quality Glossy Paper (available from Seiko Epson Corp.), Canon HR 101 High Resolution Paper (available from Canon), Canon GP 201 and GP 301 Glossy Paper (available from Canon), and Canon HG 101 and HG201 High Gloss Film (available from Canon).


A further aspect of the present invention provides a paper, an overhead projector slide or a textile material printed with an ink, a dye or by means of a process as hereinbefore defined.

A still further aspect of the present invention provides an ink jet printer cartridge, optionally refillable, comprising a chamber and an ink, wherein the ink is present in the chamber and the ink is as defined in the second aspect of the present invention.

The following examples illustrate how dyes according to the invention may be synthesised.


### Example 1

#### Preparation of



### Step 1

#### Preparation of



#### Step i)

4-aminoacetanilide-3-sulphonic acid (17.7g) was dissolved in water (300ml) and the pH was adjusted to 11-12 using lithium hydroxide (2M). The solution was carbon-screened and sodium nitrite (4.55g) added to the filtrate. The solution was then added to a mixture of ice and water to which had been added hydrochloric acid (20ml) and the mixture was stirred for 2hrs at 0-10°C. Excess nitrous acid was destroyed by the addition of sulphamic acid.

#### Step ii)

2,5-bis(2-Acetoxyethoxy)aniline (17.82g) was dissolved in acetone (200ml).

Step iii)- Coupling

The product from step ii) was added to the product of step i). Pyridine (5ml) was then added and the mixture allowed to self warm before stirring for a further 16hrs at room temperature. The product was then filtered off and washed with lithium chloride solution (500ml, 10%). The product was , filtered-off, pulled dry on the filter and used without further purification.

Step iv)

The product of step iii) was dissolved in water (500ml) by adjusting the pH to 8-9 using lithium hydroxide. The solution was screened and sodium nitrite (8.28g) added to the filtrate. The mixture was then added to a stirred solution of hydrochloric acid (20ml) in water (100ml) and stirred for 1.5hrs at room temperature before destroying excess nitrous acid using sulphamic acid.

Gamma acid (16.2g) was dissolved in water (300ml) by adjusting the pH to 10 using lithium hydroxide solution (2M). The solution was stirred at 0-10°C and the diazonium salt solution added slowly maintaining the pH at 10-10.5 throughout the addition. On completion of the addition the mixture was further stirred for 1hr at 0-10°C. Lithium chloride (30% w/v) was then added slowly and the product isolated (hot) by filtration and washed with lithium chloride solution (2l, 30%). The damp cake was slurried in acetone (1l) using a high shear mixer, filtered and washed with acetone (1l).

Step 2Preparation of the Title Product

The product from Step 1 above was dissolved in water (1l) and lithium hydroxide (80g) added. The solution was heated to 70-75°C until thin layer chromatography showed the hydrolysis to be complete (approx. 3hrs). The pH was adjusted to 8 and the solution cooled to 50°C. Lithium chloride (15% w/v) was then added slowly and the product isolated (hot) by filtration and washed with lithium chloride solution (1l, 20%). The resultant product was dissolved in water (400ml) and purified by dialysis. Evaporation of the water at 70°C gave 19.38g of the title product having a lambda max at 595nm.

Example 2-12 - Mixtures

The dye mixtures described in Table A may be prepared in which all parts are by weight and are shown in brackets. CID means C.I. Direct and CIA means C.I. Acid.

**TABLE A**

[illegible]

Inks

The inks described in Tables I and II may be prepared wherein the Dye described in the first column is the Dye or mixture made in the above example of the same number. Numbers quoted in the second column onwards refer to the number of parts of the relevant ingredient and all parts are by weight. The inks may be applied to paper by thermal or piezo ink jet printing.

The following abbreviations are used in Table I and II:

PG = propylene glycol

DEG = diethylene glycol

NMP = N-methyl pyrrolidone

DMK = dimethylketone

IPA = isopropanol

MEOH = methanol

2P = 2-pyrrolidone

MIBK = methylisobutyl ketone

P12 = propane-1,2-diol

BDL = butane-2,3-diol

CET = cetyl ammonium bromide

PHO =  $\text{Na}_2\text{HPO}_4$  and

TBT = tertiary butanol

TDG = thiodiglycol

TABLE I


Dye/ Mixture	Dye Content	Water	PG	DEG	NMP	DMK	NaOH	Na Stearate	IPA	MEOH	2P	MIBK
1	2.0	80	5		6	4					5	
2	3.0	90		5	5		0.2					
3	10.	85	3		3	3				5	1	
4	1.1	81			9		0.5				9	
5	2.5	60	4	15	3	3			6	10	5	4
6	5	65		20					10			

TABLE II

Dye/ Mixture	Dye Content	Water	PG	DEG	NMP	CET	TBT	TDG	BDL	PHO	2P	PI2
7	3.0	80	15			0.2					5	
8	9.0	90		5						1.2		5
9	1.5	85	5	5		0.15	5.0	0.2				
10	2.5	90		6	4					0.12		
11	3.1	82	4	8		0.3			5	0.2		6
12	0.9	85		10								

**CLAIMS**

1. A compound of Formula (1) and salts thereof:



Formula (1)

wherein:

A is a substituted phenyl group carrying a group of the formula  $-NR^3R^4$  and an ortho group selected from sulpho, phosphonato and phosphinato;

$R^1$  and  $R^2$  are each independently optionally substituted alkyl or optionally substituted alkoxy; and

$R^3$  and  $R^4$  are each independently H, optionally substituted alkyl, optionally substituted cycloalkyl or optionally substituted aryl, or  $R^3$  and  $R^4$  together with the nitrogen atom to which they are attached form an optionally substituted 5- or 6-membered ring.

2. A compound according to claim 1 wherein at least one of  $R^1$  and  $R^2$  carries an -OH group.

3. A compound according to any of the preceding claims wherein  $R^3$  and  $R^4$  are each independently selected from optionally substituted  $C_{1-4}$ -alkyl and optionally substituted phenyl, or  $R^3$  and  $R^4$  together with the nitrogen atom to which they are attached form an optionally substituted 5- or 6- membered ring.

4. A compound according to any of the preceding claims wherein  $R^3$  and  $R^4$  are each independently selected from  $C_{1-4}$ -alkyl,  $C_{1-4}$ -alkyl-OH, phenyl or phenyl carrying a carboxy and/or sulpho group, or  $R^3$  and  $R^4$  together with the nitrogen to which they are attached form an optionally substituted morpholino or piperidino ring.

5. A compound according to any of the preceding claims wherein the group of the formula  $-NR^3R^4$  is in the para position with respect to the azo linkage.

6. A compound according to any of the preceding claims wherein the ortho group is sulpho.

7. A compound according to any one of the preceding claims wherein  $R^1$  and  $R^2$  are each independently optionally substituted  $C_{1-4}$ -alkyl or optionally substituted  $C_{1-4}$ -alkoxy, provided that at least one of  $R^1$  and  $R^2$  carries an -OH group.

5 8. A compound according to any one of the preceding claims wherein  $R^1$  and  $R^2$  are each independently  $C_{1-4}$ -alkoxy-OH.

9. A compound according to any one of the preceding claims wherein both  $R^1$  and  $R^2$  carry an -OH group.

10 10. A compound according to any one of the preceding claims wherein one of  $R^1$  and  $R^2$  is  $-OC_{1-4}$ -alkyl-OH and the other is  $-OC_{1-4}$ -alkyl or  $-OC_{1-4}$ -alkyl-OH.

11. An ink comprising a compound according to any one of the preceding claims and a liquid medium or a low melting point solid medium.

12. An ink according to claim 11 which contains a further colorant selected from black, cyan and yellow colorants.

13. An ink according to claim 11 or 12 which contains less than 500ppm in total of divalent and trivalent metal ions.

14. A process for forming an image on a substrate comprising applying an ink according to claim 11, 12 or 13 to the substrate by means of an ink jet printer.

15. A paper, an overhead projector slide or a textile material printed with an ink according to claim 11, 12 or 13, a compound according to any one of claims 1 to 10 or by means of a process according to claim 14.

16. An ink jet printer cartridge, optionally refillable, comprising a chamber and an ink, wherein the ink is present in the chamber and the ink is as defined in claim 11, 12 or 13.